



PREFORM DUMPER SAFETY GUARD

PATENT PENDING DESIGN ELIMINATES THE NEED FOR LIGHT CURTAINS WHILE OFFERING FULL GUARDING WHEN DUMPER IS LIFTED.

~ DUMPER CANNOT BE RAISED UNLESS DOOR IS CLOSED ~

~ DOOR CANNOT BE OPENED UNTIL DUMPER IS LOWERED ~

FEATURES:

- 6' WIDTH STANDARD
- 9' DEPTH STANDARD
- 8' DOOR OPENING STANDARD
- CAT. 3 SAFETY CONTROLS FOR:
 - DUMPER DOWN POSITION
 - DOOR DOWN POSITION
- 115 VAC 6AMP POWER – NO PNEUMATIC SUPPLY NEEDED
- SAFETY EDGE STRIP ON DOOR BOTTOM
- FLOOR BOLLARDS INCLUDED
- FULL GUARDING PREVENTS OPERATOR ENTRY WHILE DUMPER IS RAISED.
- 10" BOTTOM CLEARANCE FOR EASY BROOM CLEANOUT.
- MANUAL CHAIN DOOR OVERRIDE



CONTROL OPTIONS:

- FULL AUTOMATIC – HOPPER LEVEL CONTROLS CONTROL DUMPING
- SEMI - AUTOMATIC – GUARD CONTROLS ARE TIED INTO EXISTING AUTOMATED DUMPER CONTROLS. DOOR CLOSES AND OPENS AUTOMATICALLY.
- MANUAL – FOR USE WITH HYDRAULIC JOYSTICK. A MOTOR STARTER FOR HYDRAULIC PUMP IS REQUIRED. HYDRAULIC PUMP CANNOT START UNLESS DOOR IS LOWERED.
- MANUAL – FOR USE WITH HYDRAULIC SOLENOIDS. DUMPER LIFT SOLENOID IS INTER-LOCKED.



PREFORM DUMPER SAFETY GUARD

